

Felted Automotive Floor Covering (OTOSER EMBOSSED)

Polyvinyl chloride Based Protective Floor Coating Technical Specifications;

Material	PVC Polyvinyl Chloride
Structure	Heterogeneous
Structure of Wear	Colored Wear Layer
Flooring Type	Printed Floor Covering
Structure of Wear	Smooth surface
Painting	One colour
Dimensions	Roll
Flooring Type	Heterogeneous PVC Floor Covering
Mass	2,277kg/m ²
Density	1311,7 ± 50 m ³
Thickness	1,8 mm ± 0,10

DESCRIPTION

Felt insoles, heterogeneous PVC floor covering. The polyester structure at the base and the upper protective layer are enhanced with PVC foil (15 MICRON).

USAGE PLACES

All kinds of floor coverings are laid. The linoleum is shaped by the names of printed foils and these PVC coatings are especially economical floor coverings and are preferred as flooring materials in the desired warehouses, offices, institutions, warehouses, counters, schools, hospitals. It provides slip resistance while walking on it. It has antibacterial property and is easy to clean. Depending on the application, the material should be soft or hard. For example, while it is desired to be soft in walking areas, it is preferable that the product is hard in places where material such as warehouse is placed.

BENEFITS

- It is one piece, easy to install.
- It is flexible and lightweight.
- Non-slip structure.
- Resistant to high temperatures.
- High quality aliphatic polyvinyl chloride.

APPLICATION METHOD

Surface Preparation and Application

The coating surface to be applied must be free of dust, dirt, oil and other substances that will prevent adhesion. Do not use solvent based adhesive. Do not reverse roll during application.

Felted Automotive Floor Covering (OTOSER EMBOSSED)

Polyvinyl chloride Based Protective Floor Coating

waste

2,2777 Kg/m²

PACKING

The material is wrapped in cardboard roll. Packed with polyethylene nylon material. Roll length is 18 mt. The average is 83 kg.

STORAGE

It should be stored in its unopened original package in a cool and dry environment protected from wet surfaces. In short term storage, maximum 3 pallets should be placed on top of each other and the shipment should be made with first in first out system. For long term storage, pallets should not be placed on top of each other.

SHELF LIFE

10 years from the production date under appropriate storage conditions.

SAFETY RECOMMENDATIONS

Preventive measures for the use of products should also be observed when using this product. When the work is interrupted or the work is completed, hands should be washed with plenty of water, food and drink should not be consumed, no smoking. Transport equipment must be used when transporting the product. During loading and unloading, at least two persons should assist and transport the packaged goods to the desired places.

LEGAL WARNING

The data contained in this technical document is based on our scientific and practical knowledge. Zümrüt Suni Deri Sanayi ve Tic. Ltd. Şti. is only responsible for the quality of the product. Zümrüt Suni Deri Sanayi ve Tic. Ltd. Şti. can not be held responsible. This technical document is valid until a new one is issued and invalidates the old editions.